


**Features:**

- 650V Schottky Diode
- Zero Reverse Recovery Current
- High Frequency Operation
- Positive Temperature Coefficient
- Temperature independent Switching

Benefits:

- Unipolar Rectifier
- Minimal switching loss
- Higher Efficiency
- Low cooling requirement

Symbol	Value	Unit
V_{RRM}	650	V
$I_F \text{ (} T_c=118^\circ\text{C) }$	15	A
Q_c	52	nC

Outline **Circuit****Applications:**

- Switch Mode Power Supply
- Booster diodes in PFC, DC/DC
- AC/DC converters

Maximum Ratings

Symbol	Parameter	Value	Unit	Test Conditions
V_R	DC Peak Reverse Voltage	650	V	$T_j = 25^\circ\text{C}$
V_{RRM}	Repetitive Peak Reverse Voltage	650	V	$T_j = 25^\circ\text{C}$
V_{RSM}	Surge Peak Reverse Voltage	650	V	$T_j = 25^\circ\text{C}$
I_F	Continuous Forward Current	43 34 15	A	$T_c = 25^\circ\text{C}$ $T_c = 75^\circ\text{C}$ $T_c = 118^\circ\text{C}$
I_{FRM}	Repetitive Peak Forward Surge Current	88 79	A	$T_c = 25^\circ\text{C}, T_p = 10\text{ms}, \text{Half Sine Wave}$ $T_c = 110^\circ\text{C}, T_p = 10\text{ms}, \text{Half Sine Wave}$
I_{FSM}	Non-Repetitive Peak Forward Surge Current	119 107	A	$T_c = 25^\circ\text{C}, T_p = 10\text{ms}, \text{Half Sine Wave}$ $T_c = 110^\circ\text{C}, T_p = 10\text{ms}, \text{Half Sine Wave}$
P_D	Power Dissipation	71 31	W	$T_c = 25^\circ\text{C}$ $T_c = 110^\circ\text{C}$
$T_{J,max}$	Operating Junction Temperature	175	°C	
T_{stg}	Storage Temperature Range	-55 to 175	°C	



Thermal characteristics

Symbol	Parameter	Min.	Typ.	Max.	Unit
R_{thJC}	Thermal resistance		2.1		°C/W

Electrical Characteristics

Symbol	Parameter	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
V_{DC}	DC Blocking Voltage	650			V	$I_R=100\mu A, T_J=25^\circ C$
V_F	Forward Voltage		1.55 1.9	1.8 2.2	V	$I_F=15A, T_J=25^\circ C$ $I_F=15A, T_J=175^\circ C$
I_R	Reverse Current		5 20	100 250	μA	$V_R=650V, T_J=25^\circ C$ $V_R=650V, T_J=175^\circ C$
Q_C	Total Capacitive Charge		52		nC	$Q_C = \int_0^{V_R} C dV$ $T_J=25^\circ C, V_R=400V$
C	Total Capacitance		619 96 94		pF	$V_R=1V, T_J=25^\circ C, f=1\text{ MHz}$ $V_R=200V, T_J=25^\circ C, f=1\text{ MHz}$ $V_R=400V, T_J=25^\circ C, f=1\text{ MHz}$

Typical Performance




Fig. 1 Forward Characteristics




Fig. 2 Reverse Characteristics



Typical Performance




Fig. 3 Current Derating




Fig. 4 Power Derating




Fig. 5 Capacitance vs. Reverse Voltage




Fig. 6 Recovery Charge vs. Reverse Voltage





Fig. 7 Capacitance stored Energy



Package TO-220-2L (Unit: mm)



REF.DIM	DATA BOOK mm		
	NOR	MIN	MAX
A	15.6	14.8	16.1
B	13	12.65	13.8
C	10	9.85	10.36
D	6.5	4.6	6.8
E	3.0	2.55	3.5
F			1
G	1.2	1	1.45
H	0.6	0.3	0.9
I	5.1	4.8	5.4
J	3.1	2.34	3.3
K	1.0	0.55	1.3
L	0.6	0.36	0.8
M	4.45	4.2	4.9
N	1.2	1.1	1.8
O	3.3	2.9	3.5
P	2.6	2.5	3.15
Q	3	2.9	3.5



This Product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, systems, or air-traffic control systems.

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, AZ Power Inc. disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.



5601 W SLAUSON AVE 190

CULVER CITY, CA 90230

WWW.AZPE.COM

Information in this document may change without notice. All referenced product or service names and trademarks are the property of their respective owners. Copyright © 2020 AZ Power Inc. All rights reserved.